



Ram Pump Systems

Reliable Delivery of Medium- to High-Viscosity Fluids Packaged in Pails

- Platin design minimizes leftover material and reduces waste
- Features a fluid control module for accurate monitoring and control of fluid pressure
- Integrated air controls for easy system operation and monitoring
- Integrated drum air blow-off allows for quicker material changeover with less downtime.
- Models available for tapered or straight pails.
- Compatible with a wide variety of pails, allowing more dispensing flexibility

The Dymax ram pail pump system uses a displacement pump to transfer medium- to high-viscosity fluids packaged in pails to the dispensing valve. The ram pail pump system is designed to dispense from a 5-gallon (20 L) pail and is available in two models to accommodate both straight and tapered pails. The system is designed with a platen that wipes the sides of the pail as the material level lowers. This wiping action minimizes leftover material and reduces waste, creating a more efficient dispensing process. The ram pail pump is easy to operate with integrated air controls and a fluid control module mounted directly to the system.

Specifications

Part Numbers	T21286-001 Ram Pail Pump with Straight Platen/Wiper T21286-002 Ram Pail Pump with Tapered Platen/Wiper
Pail Size	5 Gallon (20 L)
Maximum Air Input Pressure	125 psi
Ambient Operating Temp. Range (Supply System)	32-120°F (0-49°C)
Max Weight for Platen	19 lbs (8.7 kg)
Replacement Parts	T16715 Silicone Replacement Wiper T18460 Upper Bleed Purge Valve T18643 Throat Seal O-Ring Rebuild Kit T18467 Follower Plate O-Ring Seal T18612 Crossover Controls Kit





www.dymax.com

Americas

USA | +1.860.482.1010 | info@dymax.com

Europe

Germany | +49 611.962.7900 | info_de@dymax.com

Ireland | +353 21.237.3016 | info_ie@dymax.com

Asia

Singapore | +65.67522887 | info_ap@dymax.com

Shanghai | +86.21.37285759 | dymaxasia@dymax.com

Shenzhen | +86.755.83485759 | dymaxasia@dymax.com

Hong Kong | +852.2460.7038 | dymaxasia@dymax.com

Korea | +82.31.608.3434 | info_kr@dymax.com