



UVC-5 & UVC-8

UV Light-Curing Conveyor Systems

- Fast cures for high throughput
- Dependable, heavy-duty conveyor design
- Fully shielded lamp enclosures
- Qualified technical support

Dymax UVC Conveyor Systems use high-intensity UV/Visible light sources for fast curing of adhesives, coatings, and encapsulants. There are three conveyor models to match specific application requirements and budgets. These cost-efficient and versatile light-curing systems are perfect for your lab or plant.

UVC-5

The Dymax UVC-5 Conveyor System is equipped with a 120 mm-wide belt. Curing time can be adjusted by changing the belt speed from 2 meter to 26 meters-per-minute continuously. Two bulb types are available: Iron or Mercury. The Mercury system offers a half-capacity mode.



UVC-5 Specifications

Light Source	Mercury Full Capacity: 920W Mercury Half Capacity: 450W Iron Full Capacity: 910W
Power Requirements	230 V
Power	950 W
Dimensions (L x H x W)	700 mm x 299 mm x 369 mm

UVC-8

The Dymax UVC-8 Conveyor System is equipped with a 200 mm-wide belt made of Teflon® and comes with one to two UV medium-pressure bulbs (2000 W) and/or an IR-field. The distance between the bulb and the belt can be manually adjusted (between 70-120 mm) as well as the belt speed (0.5-12 m/min). Optional reflectors for curing material dispensed on temperature sensitive substrates are available.



UVC-8 Specifications

Light Source	1-2 x 2000 W
Power Requirements	3 x 400 V, 50 Hz
Power	6 kW
Dimensions (L x H x W)	1000 mm x 1200 mm x 1100 mm



www.dymax.com

Americas

USA | +1.860.482.1010 | info@dymax.com

Europe

Germany | +49 611.962.7900 | info_de@dymax.com
Ireland | +353 21.237.3016 | info_ie@dymax.com

Asia

Singapore | +65.67522887 | info_ap@dymax.com
Shanghai | +86.21.37285759 | dymaxasia@dymax.com
Shenzhen | +86.755.83485759 | dymaxasia@dymax.com
Hong Kong | +852.2460.7038 | dymaxasia@dymax.com
Korea | +82.31.608.3434 | info_kr@dymax.com

©2004-2020 Dymax Corporation. All rights reserved. All trademarks in this guide, except where noted, are the property of, or used under license by, Dymax Corporation, U.S.A.

The data contained in this bulletin is of a general nature and is based on laboratory test conditions. Dymax Europe GmbH does not warrant the fitness of the product for the intended application. Any warranty applicable to products, its application and use is strictly limited to that contained in Dymax Europe GmbH's General Terms and Conditions of Sale published on our website. Dymax Europe GmbH does not assume any responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than Dymax Corporation or act as a grant of license under any Dymax Corporation Patent. Dymax Europe GmbH recommends that each user adequately test its proposed use and application of the products before actual repetitive use, using the data contained in this bulletin as a general guide.

PB078EU 7/29/2015