

## ULTRA LIGHT-WELD® 9-20269-GEL WIRE AND COMPONENT TACKING

### INTRODUCTION

Dymax Ultra Light-Weld adhesives cure upon exposure to either UV, or high intensity visible light, in seconds. Their instant cure capability and solvent free, 100% solids composition increase productivity, lower assembly costs, and enhance worker safety. Dymax offers a complete line of UV and visible curing lamps that are matched to the adhesive's cure characteristics and a wide range of application requirements.

### DESCRIPTION

Ultra Light-Weld 9-20269-Gel photocurable adhesive is designed for fast tacking of coils, LCD's, wires and other components onto printed circuit boards (PCBs). A solvent-free, visible and UV curing adhesive, 9-20269-Gel dispenses easily and cures "on demand" for precise bonding and placement of components. Excellent adhesion to common PCB substrates, and shock absorbing capability makes it an excellent choice for a variety of electronic bonding and tacking applications. This product is in full compliance with RoHS directives 2015/863/EU.

SPECIAL FEATURES	BENEFITS
Visible Light or UV Cure Capability	Fastest cures with longwave UV lamps (365 nm) Visible light cures for UV sensitive applications (400 nm)
Thixotropic Gel Viscosity	Precise, easy dispensing, no drip, mess or stringing
Adhesion/Toughness	Flexible, resilient bonds to common electronic grade materials of construction

### UNCURED PROPERTIES

Solvent Content	None - 100% reactive solids	
Chemical Class	Urethane (Meth) Acrylate	
Appearance	Clear Gel	
Solubility	Alcohols/Chlorinated Solvents/Ketones	
Toxicity	Low	
Flash Point	>93°C (200°F)	
Viscosity (2 rpm)	200,000 cP (nominal)	ASTM D-2556
(20 rpm)	25,000 cP (nominal)	ASTM D-2556

### CURED PROPERTIES

#### PHYSICAL

Durometer Hardness	D65	ASTM D-2240
Elongation at Break	20%	ASTM D-638
Tensile at Break	2,600 psi	ASTM D-638
Young's Modulus	100,000 psi	ASTM D-638
Water Absorption (24 hr)	5.0%	ASTM D-570
Boiling Water Absorption (2 hr)	5.0%	ASTM D-570

### TYPICAL LIGHT CURE DATA

Lamp	PC-3	3010-EC
Type of Light	UV	UV
Intensity (mW/cm <sup>2</sup> )	1000 @ 365 nm	1800 @ 365 nm
Wavelength (nm) Working Range	300-500	300-500
Cure Speed (sec)		
Between Glass	<1	<<1
1/8" Bead	1-3	1
Surface Cure	2	1
Cure Depth in 1 Minute (inch)	0.25	0.30



9-20269-GEL, 06/99

## **DISPENSING AND HANDLING ADHESIVE**

Ultra Light-Weld 9-20269-Gel is packaged in a variety of containers. It may be dispensed with a variety of automatic bench-top syringe applicators or other equipment as required. For specific technical recommendations relating to dispensing and curing systems, call Dymax Technical Service at (860) 482-1010.

Repeated or continuous direct skin contact should be avoided. The use of barrier hand cream and plastic gloves are recommended. Do not wear absorbent gloves. Do not wear jewelry. Adhesive may be removed with hand soap and water. Avoid eye contact. Wipe excess wet adhesive off parts with paper towels and remove cured residue with chlorinated solvents, Freon, methanol or ethanol. See CAUTION below.

## **STORAGE AND SHELF LIFE**

Store the material in a cool, dark place when not in use. Do not expose to light. This product may polymerize upon prolonged exposure to ambient and artificial light. Keep covered when not in use. This material has an 18-month shelf life from date of manufacture, unless otherwise specified, when stored between 10°C (50°F) and 35°C (90°F) in the original, unopened container. Material can polymerize upon prolonged exposure to ambient light. Replace lid immediately after pouring. Keep covered at all other times.

## **CAUTION**

For industrial use only. Avoid breathing vapors. Avoid contact with eyes and clothing. In case of skin contact, immediately flush with water for at least 15 minutes; for eyes, get medical attention. Wash clothing before reuse. Keep out of reach of children. Do not take internally. If swallowed, vomiting should be induced at once and a physician called. For specific information, refer to the product Material Safety Data Sheet before use.

## **GENERAL INFORMATION**

This product is intended for industrial use only. Keep out of the reach of children. Avoid breathing vapors. Avoid contact with skin, eyes, and clothing. Wear impervious gloves. Repeated or continuous skin contact with uncured material may cause irritation. Remove material from skin with soap and water. Never use organic solvents to remove material from skin and eyes. For more information on the safe handling of this material, please refer to the Safety Data Sheet before use.

The data provided in this document are based on historical testing that Dymax performed under laboratory conditions as they existed at that time, and are for informational purposes only. The data are neither specifications nor guarantees of future performance in a particular application. Dymax does not guarantee that this product's properties are suitable for the user's intended purpose.

Numerous factors—including, without limitation, transport, storage, processing, the material with which the product is used, and the ultimate function or purpose for which the product was obtained—may affect the product's performance and/or may cause the product's actual behavior to deviate from its behavior in the laboratory. None of these factors are within Dymax's control. Conclusions about the behavior of the product under the user's particular conditions, and the product's suitability for a specific purpose, cannot be drawn from the information contained in this document.

It is the user's responsibility to determine (i) whether a product is suitable for the user's particular purpose or application and (ii) whether it is compatible with the user's intended manufacturing process, equipment, and

© 1997, 1998 Dymax Corporation  
MD® Medical Device Adhesives is also a registered trademark of Dymax Corporation

REV. 12/27/2018

The data contained in this bulletin is of a general nature and is based on laboratory test conditions. Dymax does not warrant the data contained in this bulletin. Any warranty applicable to the product, its application and use is strictly limited to that contained in Dymax's standard Conditions of Sale. Dymax does not assume responsibility for test or performance results obtained by users. It is the user's responsibility to determine the suitability for the product application and purposes and the suitability for use in the user's intended manufacturing apparatus and methods. The user should adopt such precautions and use guidelines as may be reasonably advisable or necessary for the protection of property and persons. Nothing in this bulletin shall act as a representation that the product use or application will not infringe a patent owned by someone other than Dymax or act as a grant of a license under any Dymax Corporation Patent. Dymax recommends that each user adequately test its proposed use and application before actual repetitive use, using the data contained in this bulletin as a general guide.

methods. Under no circumstances will Dymax be liable for determining such suitability or compatibility. Before the user sells any item that incorporates Dymax's product, the user shall adequately and repetitively test the item in accordance with the user's procedures and protocols. Unless specifically agreed to in writing, Dymax will have no involvement in, and shall under no circumstances be liable for, such testing.

Dymax makes no warranties, whether express or implied, concerning the merchantability of this product or its fitness for a particular purpose. Nothing in this document should be interpreted as a warranty of any kind. Under no circumstances will Dymax be liable for any injury, loss, expense or incidental or consequential damage of any kind allegedly arising in connection with the user's handling, processing, or use of the product. It is the user's responsibility to adopt appropriate precautions and safeguards to protect persons and property from any risk arising from such handling, processing, or use.

The specific conditions of sale for this product are set forth in Dymax's Conditions of Sale which are available at <https://www.dymax.com/index.php/en/resources/sales-terms-conditions>. Nothing contained herein shall act as a representation that the product use or application is free from patents owned by Dymax or any others. Nothing contained herein shall act as a grant of license under any Dymax Corporation Patent.

Except as otherwise noted, all trademarks used herein are trademarks of Dymax. The "®" symbol denotes a trademark that is registered in the U.S. Patent and Trademark Office.

The contents of this document are subject to change. Unless specifically agreed to in writing, Dymax shall have no obligation to notify the user about any change to its content.