



- Simple to Operate
- Set Screw Locks Lightguide in Place
- PTB and NIST Traceable

## ACCU-CAL™ 50 Radiometer

Consistent UV light curing requires periodic monitoring of UV intensity or dose. The ACCU-CAL™ 50 radiometer is simple to operate and offers repeatable measurement of UV light. The ACCU-CAL™ 50 can measure UV light emitted from lightguides (3 mm, 5 mm, and 8 mm), UV flood systems, and UV conveyors. With a spectral sensitivity from 320 to 395 nm (UVA), the ACCU-CAL™ 50 measures intensities from 1 mW/cm<sup>2</sup> to 40 W/cm<sup>2</sup>. A specially designed photo-sensor assembly protects the photo-sensor from the high temperatures sometimes associated with today's high intensity UV spot lamps.

### Three Reasons to Use a UV/Visible Radiometer

- Maintaining a Light-Curing Process – A radiometer measures whether a light-curing system is providing intensity above the “bulb change” intensity. Radiometers provide the same monitoring control for light curing processes that thermometers provide for thermal processes.
- Providing a Worker Friendly Light-Curing Process – The ACCU-CAL™ 50 is sufficiently sensitive to measure the intensity of stray or reflected UV light (as little as 1 mW/cm<sup>2</sup>). Dymax recommends that worker UVA exposure not exceed 1 mW/cm<sup>2</sup>. For reference, UV (320-395 nm) intensity on a sunny day can range from 2-6 mW/cm<sup>2</sup>.
- Measuring Transmission Rates Through Substrates – A radiometer can be used to measure the transmission rates of various wavelengths through substrates that absorb UV and/or visible light. To assure an effective curing process it is critical to measure the light intensity reaching the resin below the intervening substrate.



# Specifications

Specifications	
<b>Spectral Sensitivity</b>	320 to 395 nm
<b>Intensity Range</b>	1 mW/cm <sup>2</sup> to 40 W/cm <sup>2</sup>
<b>Resolution</b>	Intensity (1 mW/cm <sup>2</sup> ; to three significant digits) Dose (1 mJ/cm <sup>2</sup> )
<b>Calibration Period</b>	12 months
<b>Operating Temperature Ranges</b>	Optometer: +5 to +40°C Detector: 120°C continuous, Peak 200°C
<b>Measurement Modes</b>	Intensity (mW/cm <sup>2</sup> and W/cm <sup>2</sup> ) Peak Intensity (mW/cm <sup>2</sup> and W/cm <sup>2</sup> ) Dose (J/cm <sup>2</sup> )
<b>Light Sources</b>	Lightguides (3 mm, 5 mm, and 8 mm) Floods/Conveyors
<b>Power Supply</b>	Two (2) AA batteries
<b>Battery Life</b>	250 hours (automatic shutoff after 1 hour)
<b>Sensor Dimensions</b>	Photo-Sensor Diameter = 9 mm Diameter = 37 mm Thickness = 8 mm Cable Length = 1 M
<b>Meter Dimensions</b>	120 mm x 65 mm x 23 mm (Length x Width x Thickness)

## Radiometer Calibration

Dymax recommends calibrating the ACCU-CAL™ 50 radiometer annually to ensure proper operation of the instrument. Calibration services are available through Dymax. Please contact Dymax Customer Support for more information.

# Ordering Information

Product	Part Number	Description
ACCU-CAL™ 50 for Flood Lamps and Conveyors	39561	Complete radiometer ( without lightguide adapters or lightguide simulator*); includes storage/carrying case
ACCU-CAL™ 50 for Spot and Flood Lamps and Conveyors	39560	Complete radiometer with lightguide adapters (3 mm, 5 mm, and 8 mm) and lightguide simulator*; includes storage/carrying case
Flood to Spot Adapter Kit	39554	Kit includes three lightguide adapters (3 mm, 5 mm, and 8 mm) and a lightguide simulator*
Lightguide Adapter	39556	Fits 3 mm ID lightguides (5 mm OD)
	39557	Fits 5 mm ID lightguides (7 mm OD)
	39558	Fits 8 mm ID lightguides (10 mm OD)
Lightguide Simulator (5 mm)	38408	5 mm lightguide simulator with a standard D connection

\*A lightguide simulator is used to measure direct spot lamp intensity (required to calculate lightguide transmission)



ACCU-CAL™ 50 for measuring spots, floods, and conveyors PN 39560



ACCU-CAL™ 50 for measuring floods and conveyors only PN 39561

