

# Dispensing Equipment Selector Guide



# Dymax Fluid Dispensing Equipment

Dymax is committed to providing the best chemistry, curing equipment, and dispensing systems that offer customers complete manufacturing solutions for their challenging applications. Dymax, in alliance with some of the world's leading dispensing companies, has developed high-quality, field-proven dispense systems to fit many dispensing applications. These systems include various automatic and manual dispense systems, spray valves, and related components for seamless integration into your assembly process. Dymax engineers will work with you to create the best dispensing solution for your application.

- Manual and automated dispensing solutions
- Pneumatic spray valves and guns for applying coatings, lubricants, and masking resins
- Dispensing systems with adjustable suck-back control that facilitates clean, crisp shutoff even with stringy or tacky materials.
- Dispensing valves that offer contaminate-free dispensing

Model Number	Micro-Dot™	Stepper™	SD-100	200	300	400	455	826	828	475	485	775 Series	SG-100-RS	SG-100-RH	
Dispense Data	Dispense Modes	Shot	Shot	Shot (timed), Continuous (bead)	Shot (manual), Continuous (bead)	Shot (timed), Continuous (bead)	Shot (timed), Continuous (bead)	Shot (timed), Continuous (bead)	Shot, Continuous (Bead)		Shot (timed), Continuous (bead)	Shot (timed), Continuous (bead)	Shot (timed), Continuous (bead)	Spray	
	Shot Size	0.0002 – 0.25 mL (15/18 GA Taper Tip)	0.01 – 0.10 mL 0.025 – 0.10 mL 0.05 – 0.25 mL 0.10 – 1.0 mL				0.002 mL to Continuous Flow	0.003 mL (0.066" tubing) to Continuous Flow	0.005 mL	0.02 mL	0.004 mL to Continuous Flow	0.002 mL to Continuous Flow	0.01 mL to Continuous Flow	Flat: 0.75" - 2+" [1.91 cm - 5.08+ cm] Round: 0.25" - 2" [0.64 cm - 5.08 cm]	
	Viscosity Range	Medium to High	Medium to High	Low to High	Up to 5,000 cP			Medium to High	Low to High (including stringy)	High (including stringy)	Low to Medium	Low to High	Medium to High (including stringy)	<10,000 cP	>10,000 cP
	Materials*	UV Adhesives, Greases, Inks	UV Adhesives, Medical Fluids, Greases, Inks	UV Adhesives, Greases, Inks	UV Adhesives, Cyanoacrylates, Inks	UV Adhesives, Cyanoacrylates, Inks	UV Adhesives, Inks	UV Adhesives, Cyanoacrylates, Inks	UV Adhesives, Cyanoacrylates, Inks	UV Adhesives, Cyanoacrylates	UV Adhesives, Cyanoacrylates, Inks	UV Adhesives, Inks	UV Adhesives, Greases, Inks	Conformal Coatings, UV Maskants	UV Maskants
Mechanical Specs	Operation	Manual Syringe Dispenser	Manual Pipette	Powered Syringe Dispenser	Diaphragm	Diaphragm	Needle	Disposable Fluid Path			Diaphragm	Needle	Spool	Spray	
	Control	Manual Positive Displacement		Time Pressure	Manual Pressurized	Time Pressure	Time Pressure	Time Pressure			Time Pressure			Fluid Pressure, Atomization Pressure	
	Disposable Fluid Path	Yes			No	No	No	Yes			No			No	
	Controller	None		Integrated	None	DVC-345	DVC-345	DVC-345			DVC-345				
Operational Adjustments	Displacement	Displacement	Time, Pressure, Suck-Back	Flow	Flow	Flow	Over Pinch, Flow	Over Pinch, Flow, Suck-Back	Over Pinch, Flow, Suck-Back	Flow	Flow	Flow, Suck-Back	Flow		
	Electrical Required	None		90-260 VAC	None	110V (for controller only) 100-240 VAC		110V (for controller only) 100-240 VAC			110V (for controller only) 100-240 VAC				
Compressed Air Required	No		Yes	Yes	Yes	Yes	Yes			Yes			Yes		
Supply Reservoirs	3, 5, 10 cc Syringe (most brands)	1, 3, 5 cc Syringe	3, 5, 10, 30, 55 cc Syringe	Cartridge or Pressure Pot	Cartridge or Tank	Cartridge or Tank	Cartridge or Pressure Pot			Syringe, Cartridge, or Tank			Cartridge or Tank		
Valve Materials	Valve Body (non-wetted)	N/A			Delrin®	Delrin®	Delrin®	Anodized AL			SS, Anodized AL			SS	
	Wetted Path	Syringe and Tip			Delrin®	Delrin®	SS/AL	Selected Tubing			Acetal	Acetal/SS	SS/AL	SS	
	Wetted Valve Seals	N/A			Teflon®	Teflon®	Silicone	N/A			UHMW PE	Silicone	Teflon® or Viton®	Teflon®, Kalrez®	
	Tubing	N/A SD-100 needs tubing			Polyethylene	Polyethylene	Polyethylene	Polyethylene			Polyethylene	Polyethylene	Polyethylene	Polyethylene	
CE Approval			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

\* If there is any question about material compatibility, please contact Dymax Application Engineering. Valves containing disposable fluid path technology offer several choices of tubing to ensure proper compatibility with the fluid being dispensed.

## Application Overview

	Micro-Dot™	Stepper™	SD-100	200	300	400	455	826	828	475	485	775 Series	SG-100-RS	SG-100-RH
Viscosity Range**	Med-High	Med-High	Low-Med-High	Low-Med	Low-Med	Low-Med	Med-High	Low-Med-High	High	Low-Med	Low-Med-High	Med-High	Low-Med	Med-High
Microdots	•	•	•			•		•			•		N/A	N/A
Dots	•	•	•	•	•	•	•	•	•	•	•	•	N/A	N/A
Beads			•	•	•	•	•	•	•	•	•	•	N/A	N/A
Potting			•	•	•	•	•	•	•	•	•	•	N/A	N/A
Spray - Conformal Coatings													•	•
Spray - Maskants													•	•

\*\* Low Viscosity= < 1000 cP    Medium Viscosity= 1000 cP - 10,000 cP    High Viscosity= > 10,000 cP +

## Dispensing System Packages

Dymax dispensing valves can be integrated into automated dispensing systems or paired with a controller and a material reservoir to create a bench-top dispensing system. Dymax offers a variety of material reservoirs to accommodate most dispensing applications. Cartridge reservoirs, bottle drop-in reservoirs, and larger stainless steel pressure pots are available from Dymax.



Cartridge Reservoirs  
(6, 12, & 20 oz sizes)



1 Gallon Bottle  
Drop-In Reservoir



Drop-in Reservoir  
(5, 10, & 15 gallon sizes)



DVC-345 Digital Valve Controller

## Dispensing Tips




A variety of both needle and taper dispense tips in various lengths, gauges, and shapes are available from Dymax. Tip selection is critical when precision is required and the length, shape, and size of the tip used will define the shape of the fluid deposit and the performance of your dispense system. Dymax Application Engineering is available for assistance with selecting the optimal tip. Visit [www.dymax.com/dispensing\\_tips](http://www.dymax.com/dispensing_tips) to see Dymax's dispensing tip selection.

## Additional Dymax Offerings



### High-Performance Light-Curable Materials

Dymax adhesives are designed to rapidly bond glass, metal, and plastic substrates upon exposure to UV/Visible light, while providing design engineers with tools to dramatically improve manufacturing efficiency and reduce costs. Dymax solvent-free adhesives are environmentally friendly, RoHS compliant, and meet the demands of challenging applications in a variety of markets. They provide significant manufacturing advantages including reduced labor and assembly costs, improved in-line inspection with fluorescing grades, reduced WIP, shorter cycle times, fewer assembly stations, and elimination of ovens and racking.



### Light-Curing Equipment

Dymax offers a wide range of light-curing equipment for curing adhesives, coatings, maskants, and sealants. Available systems include spot lamps for small-area cure or repair, flood-lamp systems for bench-top batch curing, and conveyor systems for automated in-line curing of materials including adhesives, pastes, solvents, and coatings.



© 2012-2014 Dymax Corporation. All rights reserved. All trademarks in this bulletin, except where noted, are the property of, or used under license by Dymax Corporation, U.S.A. Teflon, Delrin, Kalrez, and Viton are registered trademarks of DuPont.

Please note that most dispensing and curing system applications are unique. Dymax does not warrant the fitness of the product for the intended application. Any warranty applicable to the product, its application and use is strictly limited to that contained in Dymax's standard Conditions of Sale. Dymax recommends that any intended application be evaluated and tested by the user to insure that desired performance criteria are satisfied. Dymax is willing to assist users in their performance testing and evaluation by offering equipment trial rental and leasing programs to assist in such testing and evaluations. Data sheets are available for valve controllers or pressure pots upon request. SG006DA 3/5/2014

Dymax Corporation  
860.482.1010  
info@dymax.com  
[www.dymax.com](http://www.dymax.com)

Dymax Oligomers & Coatings  
860.626.7006  
oligomers&coatings@dymax.com  
[www.dymax-oc.com](http://www.dymax-oc.com)

Dymax Europe GmbH  
+49 (0) 611.962.7900  
info\_de@dymax.com  
[www.dymax.de](http://www.dymax.de)

Dymax UV Adhesives & Equipment (Shenzhen) Co Ltd  
+86.755.83485759  
dymaxasia@dymax.com  
[www.dymax.com.cn](http://www.dymax.com.cn)

Dymax UV Adhesives & Equipment (Shanghai) Co Ltd  
+86.21.37285759  
dymaxasia@dymax.com  
[www.dymax.com.cn](http://www.dymax.com.cn)

Dymax Asia (H.K.) Limited  
+852.2460.7038  
dymaxasia@dymax.com  
[www.dymax.com.cn](http://www.dymax.com.cn)

Dymax Korea LLC  
82.2.784.3434  
info@dymax.kr  
[www.dymax.com.kr](http://www.dymax.com.kr)